



### Physical Dimensions

Model #	Description	A	B	C	D
3P-020-M02-DCP	Metal Bowl, Manual Drain	7.0	6.8	3.0	1.5
3P-020-M02-DC	Metal Bowl, Float Drain	7.0	6.8	3.0	1.5
3P-020-M02-DCi	Metal Bowl, Float Drain w/Indicator	7.0	7.5	3.0	1.5
3P-020-P02-DCP	Poly Bowl, Manual Drain	7.0	6.8	3.0	1.5
3P-020-P02-DC	Poly Bowl, Float Drain	7.0	6.8	3.0	1.5
3P-020-P02-DCi	Poly Bowl, Float Drain w/Indicator	7.0	7.5	3.0	1.5

### Specifications

Port Sizes	1/4"
Thread Styles	NPT, BSPT, BSPP
Flow Capacity	20 SCFM @ 100 PSI
Bowl Types	Aluminum Polycarbonate
Maximum Temp. & Pressure*	Aluminum 175°F, 200 PSIG Polycarb. 125°F, 150 PSIG
Filter Capacity	0.01 Micron and Larger
Differential Pressure	< 5.0 PSID at Rated Flow

\*For higher pressure applications, consult factory. If unit is equipped with differential indicator, maximum temperature and pressure are 125°F and 150 PSIG regardless of bowl design.

### Order Guide

	Port Size	Metal Bowl	Metal Bowl w/Indicator	Poly Bowl	Poly Bowl w/Indicator
Manual Drain	1/4"	3P-020-M02-DCP	3P-020-M02-DCPi	3P-020-P02-DCP	3P-020-P02-DCPi
Float Drain	1/4"	3P-020-M02-DC	3P-020-M02-DCi	3P-020-P02-DC	3P-020-P02-DCi

### Replacement Parts & Accessories

Description	Part Number	Description	Part Number
Bowl O-Ring	N32-95-009	Stage 1 Element	3P-020
Metal Bowl Assembly, Plastic Float Drain	N32-95-950	Blanking Cap	N32-95-020
Differential Indicator	N32-W1-DPi	Stage 2 Element	3C-020
Manual Drain	N32-95-182	Manual Flex Drain	N32-95-610
Brass Float Drain	N32-95-978	Low Flow Plastic Drain	N32-96-400
Plastic Float Drain	N32-95-973	Poly Bowl, Plastic Float Drain	N32-15-160