



# Pre-torqued Holder

**Oseco's Pre-torqued Holders provide time and cost savings during inspection**

### FEATURES

- Available in sizes from 1" through 18" in the FRDI format
- 1" through 8" in the PRDI format.
- ANSI ratings of 150# and 300# are available.
- Simply ask for either the FRDI(P) or the PRDI(P) and you will receive the best pre-torqued insert holders available.

## Pre-torqued Holder

The Pre-Torqued Insert Holders, FRDI(P) and PRDI(P), may be removed for inspection purposes and returned without disturbing the torque values placed on the rupture disc. This single feature has significant value when you consider the savings you will earn on the purchase of replacement rupture discs alone. These savings, along with the time saved by installing Oseco pre-torqued rupture disc holders, will be cost effective.



[www.oseco.com](http://www.oseco.com)

Contact Oseco at 800-395-3475 or email us at [info@oseco.com](mailto:info@oseco.com).

**FRDI(P) and PRDI(P) Pre-Torqued Insert-type Holder Dimensional Data**

Size (Inches)	O.D. (Inches)	FRDI: (Overall Height Inches)	PRDI: (Overall Height Inches)
1	3.62	1.62	1.75
1.5	4.37	1.62	1.75
2	5.0	1.62	1.75
3	6.18	1.62	1.93
4	7.62	1.87	2.31
6	9.62	2.50	2.81
8	11.87	2.87	3.43
10	14.25	3.12	-
12	17.0	3.62	-
14	19.25	3.87	-
18	23.12	5.12	-



Let us help you with all your pressure relief questions. Contact Oseco at **800-395-3475** or email us at **info@oseco.com**.

**Oseco Inc**  
1701 W. Tacoma  
Broken Arrow Oklahoma 74012 USA  
Tel: (918) 258-5626  
Fax: (918) 251-2809



Visit the products section of [oseco.com](http://oseco.com) to ensure you have the most recent information.

**[www.oseco.com](http://www.oseco.com)**