



ANALOG CHECK PIN SPECIFICATION				
ANALOG OUTPUT	OUTPUT RANGE	OUTPUT IMP.	RESOLUTION	OUTPUT CURRENT
A	±10V	100Ω	ANALOG DATA	≤1mA
B			8 BIT DIGITAL	

STATUS LED COLOR/CONDITION	DRIVE STATUS DESCRIPTION
OFF	NOT READY
GREEN	READY
RED	RUNNING
FLASHING RED (2.0Hz)	FAULT
FLASHING RED (0.67Hz)	ALARM - RUNNING
FLASHING GREEN (0.67Hz)	ALARM - STOPPED
ALTERNATING RED/GREEN (2.0Hz)	TEST MODE

REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.
6						13						20					
5						12						19					
4						11						18					
3						10						17					
2						9						16					
1						8						15					
0	06/23/06	FIRST ISSUE				7						14					

YORK INTERNATIONAL CORPORATION
YORK, PA .17405

**PCB (2)
INTERCONNECTION**

DIMENSIONS ARE IN INCHES
 DO NOT SCALE
 TOLERANCES PER ENG. STD. M-282
 WELDING PER ENG. STD. M-30
 REF. DWG.

MATERIAL _____ ENG. STD. _____
 PART NO. _____
 CUT SIZE _____

NAME _____	DATE _____	SIZE _____	CAGE NO _____	DRAWING NUMBER
DR. _____	APPR. _____	SCALE: _____	D	1808JS17
WT. = _____ LBS.		ORIG. NO. _____		SHEET 10 of 15

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED, AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART, OR DISCLOSE ANY OF THE INFORMATION UPON IT TO OTHERS WITHOUT WRITTEN RELEASE BY YORK INTERNATIONAL CORPORATION.