


**ANALOG CHECK PIN SPECIFICATION**

ANALOG OUTPUT	OUTPUT RANGE	OUTPUT IMP.	RESOLUTION	OUTPUT CURRENT
A	±10V	100Ω	ANALOG DATA	=1mA
B			8 BIT DIGITAL	

**METER**

CTR	METER			
031-02674-000	10V / %	10V / %	10V / %	10V / %

STATUS LED COLOR/CONDITION	DRIVE STATUS DESCRIPTION
OFF	NOT READY
GREEN	READY
RED	RUNNING
FLASHING RED (2.0Hz)	FAULT
FLASHING RED (0.67Hz)	ALARM - RUNNING
FLASHING GREEN (0.67Hz)	ALARM - STOPPED
ALTERNATING RED/GREEN (2.0Hz)	TEST MODE



**WARNING:**  
SIMULTANEOUS CONNECTION OF CN2 AND CN2A IS NOT PERMITTED.

REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.
6						13						20					
5						12						19					
4						11						18					
3						10						17					
2						9						16					
1						8						15					
0	06/07/06	FIRST ISSUE				7						14					

**YORK INTERNATIONAL CORPORATION**  
YORK, PA . 17405

DIMENSIONS ARE IN INCHES  
DO NOT SCALE  
TOLERANCES PER ENG. STD. M-282  
WELDING PER ENG. STD. M-30  
REF. DWG.

**PCB (2)**  
**INTERCONNECTION**

MATERIAL  
TYPE \_\_\_\_\_ ENG. STD. \_\_\_\_\_  
PART NO. \_\_\_\_\_  
CUT SIZE \_\_\_\_\_

DR. _____	NAME _____	DATE _____	SIZE _____	CAGE NO _____	DRAWING NUMBER
APPR. _____			D		1808K217
SCALE: _____			WT. = _____	LBS. _____	ORIG. NO. _____

SHEET 10 of 15