



ANALOG CHECK PIN SPECIFICATION				
ANALOG OUTPUT	OUTPUT RANGE	OUTPUT IMP.	RESOLUTION	OUTPUT CURRENT
A	±10V	100Ω	ANALOG DATA	≅1mA
B			8 BIT DIGITAL	

STATUS LED COLOR/CONDITION	DRIVE STATUS DESCRIPTION
OFF	NOT READY
GREEN	READY
RED	RUNNING
FLASHING RED (2.0Hz)	FAULT
FLASHING RED (0.67Hz)	ALARM - RUNNING
FLASHING GREEN (0.67Hz)	ALARM - STOPPED
ALTERNATING RED/GREEN (2.0Hz)	TEST MODE

REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.
6						13						20					
5						12						19					
4						11						18					
3						10						17					
2						9						16					
1						8						15					
0	06/12/09	FIRST ISSUE		XZ	AL	7						14					

**YORK INTERNATIONAL CORPORATION**  
YORK, PA . 17405

DIMENSIONS ARE IN INCHES  
DO NOT SCALE  
TOLERANCES PER ENG. STD. M-282  
WELDING PER ENG. STD. M-30  
REF. DWG.

**PCB (2)  
INTERCONNECTION**

MATERIAL  
TYPE \_\_\_\_\_ ENG. STD. \_\_\_\_\_  
PART NO. \_\_\_\_\_  
CUT SIZE \_\_\_\_\_

DR. _____	NAME _____	DATE _____	SIZE _____	CAGE NO _____	DRAWING NUMBER <b>1808MV17</b>
APPR. _____	WT. = _____		LBS. _____	ORIG. NO. _____	SHEET 10 of 15
SCALE: _____					

\*ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED, AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART, OR DISCLOSE ANY OF THE INFORMATION UPON IT TO OTHERS WITHOUT WRITTEN RELEASE BY YORK INTERNATIONAL CORPORATION.\*