



EXTERNAL VFD START/STOP RELAY

EXT
a 19G b ---
a b ---
a b ---
a b ---

DRIVE INPUT VCTT

10M1
a 19S b ---
a b ---
a b ---
a b ---
a b ---
a b ---
a b ---
a b ---
SEE RATINGS

PRE-CHARGE SHORTING VCTT

10M1A
a 19Q b ---
a b ---
a b ---
a b ---
a b ---
a b ---
a b ---
a b ---
SEE RATINGS

**YORK INTERNATIONAL CORPORATION**  
YORK, PA . 17405

DIMENSIONS ARE IN INCHES DO NOT SCALE TOLERANCES PER ENG. STD. M-282 WELDING PER ENG. STD. M-30 REF. DWG.		<b>CONTROL CIRCUIT</b>		MATERIAL TYPE _____ ENG. STD. _____	
DR. _____ APPR. _____ SCALE: _____		SIZE <b>D</b>	CAGE NO.	DRAWING NUMBER <b>1808MX20</b>	
WT. = _____ LBS.		ORIG. NO.		SHEET 13 of 15	

REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.
6						13						20					
5						12						19					
4						11						18					
3						10						17					
2						9						16					
1						8						15					
0	06/19/09	FIRST ISSUE		XZ	AL	7						14					

\*ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED, AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART, OR DISCLOSE ANY OF THE INFORMATION UPON IT TO OTHERS WITHOUT WRITTEN RELEASE BY YORK INTERNATIONAL CORPORATION.\*