



EXTERNAL VFD START/STOP RELAY

EXT
a 19G b ---
o --- b ---
o --- b ---
o --- b ---
o --- b ---

DRIVE INPUT VCTT

10M1
a 19S b ---
o --- b ---
o --- b ---
o --- b ---
o --- b ---

PRE-CHARGE SHORTING VCTT

10M1A
a 19Q b ---
o --- b ---
o --- b ---
o --- b ---
o --- b ---

**YORK INTERNATIONAL CORPORATION**  
YORK, PA . 17405

DIMENSIONS ARE IN INCHES DO NOT SCALE TOLERANCES PER ENG. STD. M-282 WELDING PER ENG. STD. M-30 REF. DWG.		<b>CONTROL CIRCUIT</b>		MATERIAL TYPE _____ ENG. STD. _____ PART NO. _____ CUT SIZE _____
DR. _____ APPR. _____ SCALE: _____	NAME _____ DATE _____	SIZE <b>D</b>	CAGE NO _____	DRAWING NUMBER <b>1808K420</b>
WT. = _____ LBS.		ORIG. NO. _____		SHEET 13 of 15

REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.	REV. LEV.	DATE	REVISION RECORD	CHG. NO.	DR.	CK.
6						13						20					
5						12						19					
4						11						18					
3						10						17					
2						9						16					
1						8						15					
0	06/23/06	FIRST ISSUE				7						14					

\*ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED, AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART, OR DISCLOSE ANY OF THE INFORMATION UPON IT TO OTHERS WITHOUT WRITTEN RELEASE BY YORK INTERNATIONAL CORPORATION.\*