

CP130

Small Footprint

Thermal Printer
CE



- Windows® Driver
- POS Compatible
- ABS Plastic
- Configurable Baud 150-57600
- Compact 5.25" L x 3.75" W
- 9-36 Volt DC or A/C
- RS-232
- Global power supply for 100/240VAC 50/60Hz or cable for direct D/C connection (optional)

VALUE IN
WEIGHING

CP130 Thermal Printer

Specifications

Size:

133.4 mm (L) x 95.3 mm (W) x 64 mm (H)
5.25" L x 3.75" W x 2.5" H

Operating Temperature:

0° C to 50° C (41° F to 104° F)

Unit Weight: 0.34 kg (0.75 lb)

Power: 9-36 VDC

Direct DC Power Cable: AWT25-501087 (optional)

A/C Power Supply: AWT05-505594 (optional)

100-240VAC, 50/60Hz, 24VDC, 1.25 amp

Baud Rate: 150 up to 57,600

Serial RS-232

Factory Default: 9600, 8, N, 1*

**Configuration cable "AWT05-505624 needed to change configuration*

Wireless Data Input: Optional Bluetooth (see manufacturer)

Paper Width: 58.4 mm (2.3")

Print Width: 48.2 mm (1.9") @ 384 dots per line

Paper Out Sensor

Data Buffer: 20K

Number of Columns: 12, 16, 24, 32, 42

**Configuration cable "AWT05-505624 needed*

Common Applications:

In-Vehicle Printer, Emergency Services, Field Service, Logistics, Testing and Measurements, Retail, Facilities Management, Agriculture, Recycling, Waste Management, Law Enforcement, Cranes, Data Collection, Receipts, Product Labelling & Hospitals



Global Power Supply: AWT05-505594



Extra Paper Media
Sold Separately



a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
Email: sales@brecknellscales.com
www.brecknellscales.com



Brecknell

Foundry Lane, Smethwick
West Midlands B66 2LP UK
Tel: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@brecknellscales.co.uk
www.brecknellscales.co.uk

